

KEMPERTEC 1K thinner



Uses

- For use in KEMPEROL 1K-PUR waterproofing, KEMPERDUR Deko and KEMPERDUR Deko transparent for low processing temperatures (between +10 °C and +5 °C)
- As liquid cover on opened containers of KEMPEROL 1K-PUR, KEMPERDUR Deko and KEMPERDUR Deko transparent
- Designed for horizontal surface features

Features

- Optimizes viscosity at low ambient temperatures
- Special combination of organic solvents

Pack sizes

500 ml in container

Shelf Life

Can be stored cool, frost-free, dry and unopened. Best before: see container label.

Properties

Form Liquid

Colour Clear

* Values obtained at a temperature of 23 °C - 50% rel. humidity. These values vary depending on the weather conditions, such as wind, humidity and temperature.

Usage guide

125 ml to maximum 250 ml for a 7 kg container of the KEMPEROL 1K-PUR waterproofing;

250 ml to maximum 500 ml for a 15 kg container of the KEMPEROL 1K-PUR waterproofing;

500 ml to maximum 1,000 ml for a 25 kg container of the KEMPEROL 1K-PUR waterproofing;

maximum 250 ml for a 6 kg container KEMPERDUR Deko;

maximum 250 ml for a 5 kg container KEMPERDUR Deko transparent.

CE marking

Component to 2

ETA 03/0043

Application

In the event of low ambient temperatures (+10 °C to +5 °C), the KEMPERTEC 1K thinner to the KEMPEROL 1K-PUR waterproofing or KEMPERDUR Deko resp. KEMPERDUR Deko transparent should be added before processing and it should be mixed well.

Personal protective equipment should be worn.

Important notes

The safety data sheets, identification of the containers, hazard statements and the safety recommendations on the containers must be observed during transportation, storage and application. The BG-Chemie technical data sheets must be observed during application.

Do not allow to enter waters, drains or to penetrate the ground.

Disposal

Liquid

EWC 07 01 04

General information

No substances of other systems may be mixed into the products of the KEMPER SYSTEM.

Only for commercial use.

Our technical data sheets / technical information and application instructions reflect the current level of knowledge in our company and the experience with our products. In each case, the new edition supersedes the previous technical information and renders it invalid. It is therefore necessary that you always have to hand the current

code of practise. The latest version can be retrieved from the KEMPER SYSTEM Login section. When using our products, a detailed, object-related and qualified inspection is required in each individual case in order to determine whether the product and /or application technology in question meets the specific requirements and purposes. We are liable only for our products being free from faults, and this only if our relevant product has been used and applied according to the instructions in our technical data sheets. Correct application of our products therefore falls entirely within the scope of liability and responsibility of the user (contractor). Our products are sold exclusively on the bases of our conditions of sale and delivery.

Issued: Vellmar, 2021-03-15